

TECHNICAL INFORMATION

F.E White PVC Static

Description :

These are hologram PET film and semi-permanent adhesive. It is designed for indoor digital imaging graphics with its service max 3years (but is dependent on the work areas) and Also for Solvent, Eco solvent, UV inkjet printing.

Performance & Physical data :

- Surface finish : Glossy
- Thickness : 0.15mm (not including adhesive)
- Tensile strength : 38.0N/10mm (KS A 1107 : 2004)
- Service life : 3years from factory (not excessive condition / with original package)
- Application temperature : 10 C to 40 C (on clean , dry substrate)
- Service temperature : -15 C to 70C (on clean, dry substrate)
- Dimensional stability : max.3% shrinkage (70 C x 48hr)
- Release paper : Silicon coated PET 38mic
- Size : 1050mm x 50M/roll
- Adhesive : static cling
- Adhesive strength : 2.0N/10mm (KS A 1107 : 2004)

Remarks and Sales conditions :

These technical information and statements made by Han Yang Co.,ltd. are based on tests to be reliable and the accuracy is not guaranteed. Just seller and manufacturer are responsible for product quantity from its proved defective.

Before use the vinyl :

- Dry for at least 2days after printing it prior to any other application.
- Avoid any factor like dusty, dirty, oily etc affecting its quality.
- Test the vinyl actually enough to get the guaranteed quality level.