



3D Lamination Film Technical Information

Specification	Description	
Film	Type	PP PP transparent film
	Thickness	75±10um
	Surface	3D-lenticular (cat eyes)
	Pattern	3D-03
Adhesive	Type	Clear solvent based permanent pressure sensitive glue
	Weight(g/m ²)	22±2
	Adhesion Temperature	15°C~40°C
	180° Peeling Force	≥8N/25mm
	Initial Adhesion-Ball Tack	≥5# Steel Ball
	Holding Power	≥800min
Liner	Type	PE Kraft paper
	Color	White
	Weight	120g±5g/m ²
	Release Force	0.1~0.6N/4cm
Storage Period	12 months under ordinary condition at temperature of 22°C and relative humidity of 50-55%	
Application	Overlaminating media for the printed graphics for 3D visual effect..	

Warranty and Limitation

Flex-Europa products are manufactured with high quality raw materials and advanced technology & equipment, guaranteed by serious and scientific quality control system. All Flex-Europa products are warranted to be free of defects in materials and manufacture at the time of shipment and to meet the product specification. Should there is any product defects caused by manufacturer, compensation will be limited within certain product price. Data above are updated results and conclusions of test by Flex-Europa and is subject to change without prior notice.

Flex-Europa is not responsible for all the performance of this material for a given application, the users of materials should perform their own testing to determine the suitability of the material for the intended use.